

# MATTRESS LAMINATION

**SW1087**

**Application:** Designed for bonding cotton and nonwoven fabric, foam, and other materials used in mattress manufacturing.

**Characteristics:** Provides superior adhesion to non-woven materials, foam, and fabrics. Offers high hot tack with good penetration, excellent heat resistance, and long-lasting durability.

**Specification:**

|                               |                                     |
|-------------------------------|-------------------------------------|
| Polymer basis                 | Polyolefin                          |
| Viscosity<br>at 180°C (mPa s) | 2,500                               |
| Softening point               | 120°C                               |
| Supply form                   | Translucent clear<br>pillows        |
| Application temperature       | 150 - 170°C                         |
| Process                       | spray / slot nozzles<br>applicators |

**Packaging & Storage:** in a 25 kg box. 40 boxess/ pallet

Shelf life of 24 months, in original package, cool and dry.

**Remarks:** All data indicated are characteristics represented as average values. Our technical data sheets are revised to represent the latest information. This edition is valid on the date of compilation.

TIANJIN SHENG-WANG ELECTRONIC  
CHEMICAL PLANT

E-mail: [sales@swadhesive.com](mailto:sales@swadhesive.com)

[www.swhotmeltglue.com](http://www.swhotmeltglue.com)

**FREE BIRD**   
Adhesives