

**EDGE BANDING HOT MELT****SW816A**

**Application:** Premium option for high-speed automatic machines, suitable for a variety of edgebands (i.e. PVC, ABS, paper, and veneer).

**Characteristics:** Provides excellent bonding capabilities, very high bond yield, with virtually invisible bondline. (Reference to Jowat 288.70)

**Specification:**

|                                |                          |
|--------------------------------|--------------------------|
| Polymer basis                  | Ethylene-Vinyl Acetate   |
| Viscosity<br>at 200 °c (mPa s) | 50,000 - 60,000          |
| Softening point                | 90 - 100 °c              |
| Supply form                    | Opaque white<br>granules |
| Application temperature        | 180 - 210 °c             |

**Packaging & Storage:** in a 25 kg kraft bag. 40 bags/ pallet  
Shelf life of 24 months, in original package, cool and dry.

**Remarks:** All data indicated are characteristics represented as average values. Our technical data sheets are revised to represent the latest information. This edition is valid on the date of compilation.

**TIANJIN SHENG-WANG ELECTRONIC  
CHEMICAL PLANT**

E-mail: [sales@swadhesive.com](mailto:sales@swadhesive.com)

[www.swhotmeltglue.com](http://www.swhotmeltglue.com)

**FREE BIRD**   
Adhesives